DATA SHEET

Phoenix XQ 350 puls CG EX

090-005647-00068



- MIG/MAG inverter welding machine including Expert XQ 3.0 control, pulse, with integrated wire feeder
- Perfect MIG/MAG weld seams even with long welding leads
- Synergic control with one-knob operation
- all in **No need to purchase additional characteristics – all characteristics for this machine type are included in the scope of delivery ex works**
  - With innovative EWM Synergic characteristics rootArc® XQ/rootArc® puls XQ, forceArc® XQ/forceArc® puls XQ, pulse/superPuls and Positionweld for aluminium
  - To find out more about our high-tech MIG/MAG arcs, please click on XQ-Process
  - Synergic characteristics for MIG/MAG standard or pulsed welding for steel/CrNi/aluminium
  - Synergic characteristics for flux-cored wires
  - Non Synergic operation for manual setting of welding parameters
  - Also suitable for MMA welding, TIG welding and gouging
  - Individually configurable programs for JOBs (welding tasks)
  - Powerful, high-precision EWM eFeed 4-roll wire feeder to reliably feed all solid and flux cored wires
  - Adjustable start and end-crater functions
  - Infinitely adjustable arc dynamics (choke effect)
- **Your benefits**
  - flexFit casing system: Many accessory parts and options can be fixed to the welding machine using conventional slot nuts
  - LED information bar: Indicates the current operating status
  - Energy-saving thanks to high efficiency and standby function
  - Best suited for use with long hose packages
  - Connection capability for remote control and function torch
  - Easy, tool-free change of welding polarity
  - Insulated wire space
  - IP23 spray water protected
  - Optional network connectivity with the ewm Xnet software via an integrated or external gateway
  - PC interface for PC300 XQ software
  - The high 1500 W cooling capacity, high-performance centrifugal pump and 8-litre coolant tank make for excellent torch cooling, resulting in cost savings on consumables
  - Free WPQR package for certification up to and including EXC2 in accordance with EN 1090 and for welding of unalloyed steels up to and including S355

© 2026 / subject to technical changes / Status: 2026-11-03 / Page 1 of 2

DATA SHEET

Phoenix XQ 350 puls CG EX

Version	Phoenix XQ 350 puls CG EX3.0 R1 5m
Setting range for welding current	5 A - 350 A
Duty cycle 40 °C	350 A / 80 %
	320 A / 100 %
Open circuit voltage	82 V
Mains voltage (ex works)	3 x 380 V - 400 V
Mains voltage (possible)	3 x 440 V - 460 V
Mains voltage (possible)	3 x 480 V - 500 V
Mains tolerances (ex works)	-25 % up to +20 %
Mains frequency	50 Hz / 60 Hz
Recommended generator power	18.8 kVA
Efficiency	90 %
Power consumption Pi	32 W
Wire feed speed	0.5 m/min - 25 m/min
	19.685 ipm - 984.253 ipm
Factory-installed roll equipment	1,0-1,2 mm UNI / Steel
Spool diameter	D200/D300
Torch connection	Euro torch connector
Tank capacity	8 l
Protection classification	IP23
Test mark	CE UKCA EAC S
EMC class	A
Dimensions (L x B x H)	1152 mm x 686 mm x 976 mm
	45.4 inch x 27 inch x 38.4 inch
Weight	113.4 kg / 250 lbs
Standards	IEC 60974-1, -5 and -10 CL.A

Configurations

Item no.	Designation
090-005647-00000	Phoenix XQ 350 puls C. Multiprocess MIG/MAG pulse welding machine including all characteristics and welding processes,
092-003305-00000	OW F06G. Gas cooling
092-003314-00000	OW NDGC F.06 C. No gas control
092-003316-00000	OW F06R1. Wheel kit with single cylinder mount
092-003349-00000	OW MCord 6 mm² 5m. Mains connection lead, 5 m
092-003749-00000	OW NVRD F06 C. No open circuit voltage reduction
092-003843-00000	OW NWHS F06 C. No wire spool heating
092-003844-00000	OW N2 DV XQ C. Without connection capability for an external wire feeder to XQ compact welding machines
092-004768-00000	OW Expert 3.0 MIG/MAG. Expert 3.0 control
092-008215-00000	OW CEE 32A. Mains plug, assembled

© 2026 / subject to technical changes / Status: 2026-11-03 / Page 2 of 2